



Auswahltabelle für Hydraulikschläuche

Nenn- durch- messer	6	8	10	12	16	20	25	32	40	50	Nenn- durch- messer
	Zoll Size	1/4" -4	5/16" -5	3/8" -6	1/2" -8	5/8" -10	3/4" -12	1" -16	1 1/4" -20	1 1/2" -24	
Schlauch- Typ	Maximaler Arbeitsdruck in bar										Norm Bez.
101	25	20	20	16	16	12	12				1 TE
102	75	68	63	58	50	45	40	35			2 TE
103	145	130	110	93	80	70	55	45	40	33	3 TE
150	225	215	180	160	130	105	88	63	50	40	1 SN
153	225	215	180	160							Werknorm
170	300	295	275	240	190	155	140				Werknorm
250	400	350	330	275	250	215	165	125	90	80	2 SN
255	400	350	330	275	250	215	165				2 SC
450	450		445	415	350	350					4 SP
460					450	420	380	325	290	250	4 SH
470						420	420	420	420		R 15
650								345	345	345	R 13 6 SP
707	190	170	155	135							R 7
709	345	310	275	240							R 8
704						21	17	14	10	7	R 4
808	255	210	175	145	115	85	60				TEF

Den aktuellen Mindestberstdruck entnehmen Sie bitte der jeweiligen Schlauchtabelle!